

Blending/Feeding



Storage



Conveying



Drying



Blending/Feeding



Heat Transfer



Size Reduction



Upstream



Downstream

Gravimetric Batch Blenders

TrueBlend™ TB45-4.....	B-1
TrueBlend™ TB100-4.....	B-5
TrueBlend™ TB250-4 and TB250-6.....	B-9
TrueBlend™ TB250R-4	B-13
TrueBlend™ TB500-4 and TB500-6.....	B-17
TrueBlend™ TB900-4 and TB900-6.....	B-21
TrueBlend™ TB1800-4, TB1800-5 and TB1800-6.....	B-25
TrueBlend™ TB2500-4, TB2500-5 and TB2500-6.....	B-29
TrueBlend™ TB3500-4, TB3500-5 and TB3500-6.....	B-33

High Heat Gravimetric Batch Blenders

TrueBlend™ TBI (H)100-900	B-37
---------------------------------	------

Extrusion Control Blender

TrueBlend™ EXT	B-41
----------------------	------

Continuous Gravimetric Blenders

TrueWeigh™ Continuous Blender	B-47
-------------------------------------	------

Blender Reporting Software

TrueBlend™ Reporting Software	B-53
SQL Reporting Software	B-55

Intelligent Weigh Scale

TrueRate™	B-57
-----------------	------

Accessories

SB-1 to SB-5 Upgrade Kit	B-60
Level Alarm Control.....	B-62
WSB/GB Retrofit Control	B-64

Feeders

TrueFeed™ TF Models.....	B-66
TrueFeed™ Touch Control Models	B-70
TrueFeed™ MicroFeeder	B-72
BFS and BFH at-the-throat models	B-74

Intermixer

Material Mixer	B-78
----------------------	------

Floor Stands

TBBS Models.....	B-80
FS Models.....	B-81

Blending / Feeding Quick Reference

Models	Batch Size lb {g}	Maximum Number Materials	Maximum Number Additives	Throughput Range lb/hr																		
				250	500	1000	1500	2000	2500	3000	3500	4000	5000	6000	7000	8000	9000	10,000	11,000	12,000		
Gravimetric Batch Blenders																						
TrueBlend™ TB45-4*	1.0 {450}	4	2																			
TrueBlend™ TB100R-4*	2.2 {1000}	4	2																			
TrueBlend™ TB250R-4*	5.5 {2500}	4	2																			
TrueBlend™ TB250-4 and TB250-6	5.5 {2500}	4	2																			
		6	4																			
TrueBlend™ TB500-4 and TB500-6	11 {5000}	4	2																			
		6	4																			
TrueBlend™ TB900-4 and TB900-6	20 {9000}	4	2																			
		6	4																			
TrueBlend™ TB1800-4, TB1800-5 and TB1800-6	40 {18,000}	4	0																			
		5	2																			
		6	4																			
TrueBlend™ TB2500-4, TB2500-5 and TB2500-6	55 {25,000}	4	0																			
		5	2																			
		6	4																			
TrueBlend™ TB3500-4, TB3500-5 and TB3500-6	77 {35,000}	4	0																			
		5	2																			
		6	4																			

TrueWeigh Continuous Blenders																						
TrueWeigh TWB07-4 Direct Weigh Hopper No Weigh Hopper	4	4																				
	4	4																				
TrueWeigh TWB07-6 Direct Weigh Hopper No Weigh Hopper	6	6																				
	6	6																				
TrueWeigh TWB30-4 Direct Weigh Hopper No Weigh Hopper	4	4																				
	4	4																				
TrueWeigh TWB30-6 Direct Weigh Hopper No Weigh Hopper	6	6																				
	6	6																				

Also, see TrueBlend High Heat Models TBA/TBH100-900

*Removable additive bins

TrueBlend Accessories	Output Range
Throat Adapters	TB45, TB100R, TB250R, TB250, TB500, TB900, TWB07, TWB30
Surge Bin Stand	B45, TB100R, TB250R, TB250, TB500, TB900, TWB07, TWB30
Material Drain Chutes	TB45, TB100R, TB250R, TB250, TB500, TB900
Level Alarm Control	All models, standard in TWB control

TrueBlend Options	
Integral Loader Control/Quick Clean Enhanced Flow Package	All TB models
Control Cable Extensions	All TB models
Loader Drop Cable with Connector	All TB models
Remote Demand Sensor	Remote mount models only
Air Blow-off for Mix Chamber Level Sensor	All TB models
Minor Component Flow Restrictor	TB100 - TB3500
Major Component Flow Restrictor	All TB models
TrueBlend Reporting Software	All TB models
Extrusion Control	All models, including TWB models
SB-3 Controller	All models
Self-Clean	All TB models
High-Temperature	All TB models, all TWB models

Feeders	Hopper Volume	Motor (rpm/Hp)	Output Range
Gravimetric TF1	0.2 ft³	0.1-200 rpm / 1/10 Hp	0.11 to 280 lbs/hr {0.05 to 126 kg/hr or 0.01 to 35 g/s}
Volumetric BFS	0.4 ft³	0-170 rpm / 1/8 Hp	0.04 to 164 lbs/hr {0.04 to 74 kg/hr or 0.01 to 21 g/s}
Volumetric BFH	0.6 ft³	0-170 rpm / 1/8 Hp	0.10 to 822 lbs/hr {0.07 to 373 kg/hr or 0.02 to 111 g/s}